

	Swift 43E	Swift 43BM	Swift 50E	Swift 50BM	Swift 50BTR
MAX. CAPACITÀ DI LAVORO MAX WORKING CAPACITY [m ² /h]	1350	1350	1500	1500	1750
CORSIA LAVORO WORKING WIDTH [mm]	450	450	500	500	500
LARGHEZZA TERGIFUIMENTI SQUEEGEE WIDTH [mm]	800	800	800	800	800
DIAMETRO SPAZZOLE BRUSH SIZE [mm]	1 x 430	1 x 430	1 x 480	1 x 480	1 x 480
GIRI SPAZZOLA BRUSH SPEED [G/min.] [R.P.M.]	150	150	150	150	150
PRESSIONE SPAZZOLE BRUSH PRESSURE [Kg]	22	22	25	25	25
MOTORE SPAZZOLA BRUSH MOTOR [V]/[W]	230/550	24/250	230/550	24/250	24/250
MOTORE ASPIRAZIONE SUCTION MOTOR [V]/[W]	230/1000	24/480	230/1000	24/480	24/480
TRAZIONE TRACTION	Meccanica Mechanical	Meccanica Mechanical	Meccanica Mechanical	Meccanica Mechanical	Automatica Automatic
MOTORE TRAZIONE TRACTION MOTOR [V]/[W]					24/200
MAX VELOCITÀ MAX SPEED [Km/h]					3,5
DEPRESSIONE SUCTION PRESSURE [mm/H ₂ O]	1700	1280	1700	1280	1280
SERBATOIO SOLUZIONE SOLUTION TANK CAPACITY [lt]	40	40	40	40	40
SERBATOIO RECUPERO RECOVERY TANK CAPACITY [Stop/Tot.][Lt]	50/55	50/55	50/55	50/55	50/55
ALIMENTAZIONE POWER SUPPLY	220/240 V - 50 Hz	2 x 12V Batterie Batteries	220/240 V - 50 Hz	2 x 12V Batterie Batteries	2 x 12V Batterie Batteries
MAX AUTONOMIA MAX. AUTONOMY [ore] [h]		2 + 3		2 + 3	2 + 3
PESO MACCHINA (SENZA BATT.) MACHINE WEIGHT (WITHOUT BATT.) [kg]	105	65	108	68	75
RUMOROSITÀ NOISE LEVEL [db]	<70	<70	<70	<70	<70
DIMENSIONI [Lun./Lar./Alt.] DIMENSIONS [Len./Width/Height]	1140/500/985	1140/500/985	1140/550/985	1140/550/985	1140/550/985

Dati e caratteristiche non sono impegnativi e possono variare senza preavviso Data and specifications are not binding and may be altered without prior notice



SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT SWIFT

C T M

via della Lora 42 - 50031 Barberino del Mugello - Firenze - Italy

tel.: (+39) 055 8418550 fax: (+39) 055 841201